

1 SIM card gateway / 2xRJ11**Voice Features**

- GSM wireless connection
- High and clear voice
- Intelligence SIM card safety management
- Standard anti pole output
- The signal strength show on the LCD
- Broad electric voltage circulates, low power depletion
- Support various power supply back ups: storage battery,
- NIMH, LION, dry battery (not included / optional)
- Caller ID, Intelligent dialing, etc.

Specifications

Ports: 2 x RJ11

Air interface standard: GSM 900/1800 MHz Phase 2+

Frequency ranges:

GSM900:

- Transmit: 890~915MHz; GSM1800:
- Receive: 935~960MHz Transmit: 1710~1785MHz;
- Channel space: 200KHz Receive: 1805~1880MHz
- Sensitivity: -104dB

· Peak power consumption: 2W

· Operating environment requirements:

Temperature: 0°C - +40°C

Relative humidity: 45% - 90%

· Connectors: SMA antenna connector (TNC optional)

· Atmospheric pressure: 86~106Pka

· Power consumption: static≤25 mA, emission≤500 mA

· Antenna: Gain: 3.5dB (all directions)

12dB(certain/selective)

· Power supply:

AC220V±10% 47-54Hz AC110V/60Hz

DC12V (not included / optional)

Back up power supply: NIMH, LION, storage battery, dry battery(not included / optional)

Talking time: 3 hours

Standby time: 18 hours