

IP521

WEB-interface

IPshop.dk



IP Phone

Current State

Network

[WAN Config](#)

[LAN Config](#)

VoIP

[SIP Config](#)

[IAX2 Config](#)

Advance

[DHCP Server](#)

[NAT](#)

[Nat Service](#)

[Firewall](#)

[QOS](#)

[SIP](#)

[Digital Map](#)

[Call Service](#)

[MMI Filter](#)

[Audio Settings](#)

[VPN](#)

Dial-peer

Config Manage

[Save Config](#)

[Clear Config](#)

[Backup Config](#)

Update

System Manage

[Account Manage](#)

[Phone Book](#)

[Syslog Config](#)

[Time Set](#)

[Reboot](#)

Running Status

Network

WAN	Connect Mode	DHCP	MAC Address	00:09:45:54:bd:a2
	IP Address	192.168.1.5	Gateway	192.168.1.1
LAN	IP Address	192.168.11.1	DHCP Server	ON

VoIP

Default Protocol:IAX2

	Register Server	musimi.dk	Proxy Server	
SIP	Register	ON	State	Registered
	SIP Stun	OFF		
IAX2	IAX2 server	gw1.fonet.dk	Register	ON
	State	Registered		

Phone Number

Public SIP	46932377
Private SIP	501
IAX2	77344722

Version: VOIP PHONE V1.6.61.52 Dec 24 2007 17 :50:59

IP Phone

- Current State
- Network
 - WAN Config
 - LAN Config
 - VoIP
- Advance
- Dial-peer
- Config Manage
- Update
- System Manage

WAN Configuration

Active IP	Current Netmask	MAC Address	Current Gateway
192.168.1.5	255.255.255.0	00:09:45:54:bd:a2	192.168.1.1

Mac Authenticating Code **Valid MAC**

VLAN Enable

Static
 DHCP
 PPPOE

Static	IP Address	192.168.1.179	Netmask	255.255.255.0
	Gateway	192.168.1.1		
DNS	Primary DNS	202.96.134.133	Alternate DNS	202.96.128.68
	DNS Domain		Auto DNS	<input checked="" type="checkbox"/>

PPPOE Server ANY

Username user123

Password

IP Phone

- Current State
- Network
 - WAN Config
 - LAN Config
 - VoIP
- Advance
- Dial-peer
- Config Manage
- Update
- System Manage

LAN Configuration

Bridge Mode

IP 192.168.11.1

Netmask 255.255.255.0

DHCP Service

NAT

If you modify Bridge Mode,Ip or Netmask,the device will auto save and reboot !

Apply

IP Phone

- Current State
- Network
 - WAN Config
 - LAN Config
 - VoIP
 - SIP Config
 - IAX2 Config
- Advance
- Dial-peer
- Config Manage
- Update
- System Manage

SIP[Registered] Configuration

Register Server Addr	ipptec.com	Proxy Server Addr	
Register Server Port	5060	Proxy Server Port	
Register Username	90603521	Proxy Username	
Register Password		Proxy Password	
Domain Realm	ipptec.com	Local SIP Port	5060
Phone Number	90603521	Register Expire Time	60 seconds
Display Name	90603521	User Agent	Voip Phone 1.0
Encrypt Key		Server Type	common <input type="checkbox"/>
DTMF Mode	DTMF_RFC2833 <input type="checkbox"/>	RFC Protocol Edition	RFC3261 <input type="checkbox"/>
Detect Interval Time	60 seconds	<input checked="" type="checkbox"/> Enable Register	

Apply

IP Phone

Current State

Network

[WAN Config](#)
[LAN Config](#)

VoIP

[SIP Config](#)
[IAX2 Config](#)

Advance

[DHCP Server](#)
[NAT](#)
[Nat Service](#)
[Firewall](#)
[QOS](#)
[SIP](#)
[Digital Map](#)
[Call Service](#)
[MMI Filter](#)
[Audio Settings](#)
[VPN](#)

Dial-peer

Config Manage

Update

System Manage

IAX[Unregistered] Configuration

IAX Server Addr

IAX Server Port

4569

Account Name

Account Password

Phone Number

Local Port

4569

Voice mail number

0

Voice mail text

mail

Echo Test number

1

Echo Test text

echo

Refresh Time

60

Seconds

Enable Register

Enable G.729

IAX(Default Protocol)

Apply