



100 users / 10 proxy

Ethernet Port 1 WAN +
1LAN

NAT Router

Codec G.711, G.729,
G726, G.723, GSM
voice codec

The PX100 IP-PBX combines complete IP-PBX features with standards based SIP for telephony solution that can stand alone or integrate with existing phone systems. PX100 is an embedded system with built-in SIP Proxy Server and NAT router for SOHO user not only provide network function but also provide an IP PBX feature in office.

PBX Features :

Trunk

- Multiple Service Providers Lines / SIP Accounts Support (10)
- Simultaneous Trunk Links: 10 concurrent trunk calls
- By adding external FXO analog gateway to use PSTN trunk Line
- By adding external GSM VoIP gateway to use GSM trunk line

Extensions

- Built-in SIP Proxy Server Following RFC-3261
- Support password authentication using MD5 digest and RFC2833 for DTMF Relay
- 100 extensions registration.
- Support 30 inbound/outbound concurrent calls

Configurable Call Routing (Dial Plan)

- Least Cost Routing
- Call Hunting ALL / Round Robin

Call Detail Records

Extensions Status Monitor

- Register Status
- Talking Status

Call hold / call waiting / 3 way conference

Forwarding - unconditional / unavailable / busy for Each Extension

Group based call pick-up

Call parking

IVR/Auto Attendant

- Configurable IVR prompts (Optional*)
- Configurable IVR Menu
- Customized Greeting
- Music on Hold

Voice Mail

- Mail Box Access Control (PIN)
- Multi-lingual (Optional**)
- 20 minutes recording time
- MWI notification
- Voice mail to e-mail

*) contact sales@ipshop.dk (MOQ 25)

***) contact sales@ipshop.dk